

Product data sheet

BKD150-D-MA(D₁)-(D₂)

Bajonet-system cover in collar technique



Advanteages and benfits:

- Elastic connection in collar technology
- For connection of empty conduit and cable protection systems (e.g. KSS150, KSS125, KSS110, KSS80)
- Compatible with other marketable systems
- For smooth-walled and corrugated pipes

Technical details:

- gas and water-tight up to 0.5 bar (corrugated pipes)
- gas- and watertight up to 1 bar (KSS(A)-S)
- gas- and watertight up to 2.5 bar (KSS150-S-PRO)
- Suitable for BKD150 wall inserts and BKD150-AF mounting flange
- Test certificates Lloyd's Register

Materials:

cover and clamping nut (PC), collar (EPDM), tensioning straps (V2A)

Variants:



Product name	Clamping range	KSS hose
BKD150-D-MA65-75	65 – 75 mm	–
BKD150-D-MA75-90	75 – 90 mm	KSS80-S
BKD150-D-MA100-110	100 – 110 mm	–
BKD150-D-MA115-125	115 – 125 mm	KSS110-S
BKD150-D-MA130-145	130 – 145 mm	KSS125-S
BKD150-D-MA150-160	150 – 160 mm	–
BKD150-D-MA160-170	160 – 170 mm	KSS150-S KSS150-S-PRO